

US006300976B1

(12) United States Patent

Fukuoka

(10) Patent No.: US 6,300,976 B1

(45) **Date of Patent:** *Oct. 9, 2001

(54) DIGITAL IMAGE CAPTURING DEVICE HAVING AN INPUT/OUTPUT INTERFACE THROUGH WHICH THE DEVICE IS CONTROLLED

(75) Inventor: Hiroki Fukuoka, Yokohama (JP)

(73) Assignee: Ricoh Company, Ltd., Tokyo (JP)

(*) Notice: Subject to any disclaimer, the term of this

patent is extended or adjusted under 35

U.S.C. 154(b) by 0 days.

This patent is subject to a terminal dis-

claimer.

(21) Appl. No.: 09/562,324

(22) Filed: May 1, 2000

Related U.S. Application Data

(63) Continuation of application No. 08/535,562, filed on Sep. 28, 1995, now Pat. No. 6,104,430.

(30) Foreign Application Priority Data

(51) Int. Cl. ⁷		H04N 5/76; H04N 7/00
Sep. 28, 1994	(JP)	6-233291

348/207, 222, 231, 232, 233, 373, 375, 376, 552; 396/310, 312, 321, 322, 419, 429; 386/95, 96, 104, 107, 108; 711/100, 103, 115; H04N 7/00, 5/76, 5/225

(56) References Cited

U.S. PATENT DOCUMENTS

4,531,161	7/1985	Murakoshi .
4,746,993	5/1988	Tada .
4,853,733	8/1989	Watanabe et al.
5,032,918	7/1991	Ota et al
5,034,804		Sasaki et al
5,040,068	8/1991	Parulski et al

5,062,010	10/1991	Saito .
5,099,262	3/1992	Tanaka et al
5,138,459	8/1992	Roberts et al
5,146,353	9/1992	Isoguchi et al
5,231,501	7/1993	Sakai .
5,295,077	3/1994	Fukuoka .
5,343,243	8/1994	Maeda .
5,367,332	11/1994	Kerns et al

(List continued on next page.)

FOREIGN PATENT DOCUMENTS

3-268583	11/1991	(JP) .
4-980	1/1992	(JP) .
5-167979	7/1993	(JP) .

OTHER PUBLICATIONS

Ricoh Digital Electronic Still (Video) Camera. Instruction Manual for Using DC-1., 9 pages. Ricoh DC-1. Brochure. May, 1995., 8 pages.

Primary Examiner—Wendy R. Garber Assistant Examiner—Ngoc-Yen Vu (74) Attorney, Agent, or Firm—Oblon, Spivak, McClelland,

(57) ABSTRACT

Maier & Neustadt, P.C.

A digital image capturing device which communicates through an input/output interface with an external processing device which monitors and/or controls the camera. The image capturing device communicates with the external device in order to output status information to the external device, receive commands from the external device and to transfer images and sound between the image capturing device and the external device. Various parameters describing the state of the image capturing device are transmitted to the external device including characteristics of the captured images, whether the flash is ready, the state of the device battery, whether the memory is full, or the parameters used when capturing images. The commands which can be sent from the external device to the image capturing device include commands to change any of the parameters of the image capturing device and a command to capture an image or a series of images, and whether or not sound is recorded.

19 Claims, 12 Drawing Sheets

